


PIN	SYMBOL	PIN	SYMBOL
1	LEDK	28	R0
2	LEDK	29	R1
3	LEDA	30	R2
4	LEDA	31	R3
5	YU(Y1)	32	R4
6	XR(X1)	33	R5
7	NC	34	R6
8	/RESET	35	R7
9	SPENA	36	HSYNC
10	SPCLK	37	VSNC
11	SPDAT	38	DCLK
12	B0	39	NC
13	B1	40	NC
14	B2	41	VDD
15	B3	42	VDD
16	B4	43	YD(Y2)
17	B5	44	XL(X2)
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	SEL2
22	G2	49	SEL1
23	G3	50	SELO
24	G4	51	NC
25	G5	52	DE
26	G6	53	GND
27	G7	54	GND

LT035A-02AT

Notes:

- 3.5" Transmissive, Normally-White TFT LCD Module
- View Direction: 6:00
- LCD Drivers: HX8238-D
- Interface: 24-Bit RGB/8-BIT RGB/CCIR656/CCIR601
- Touch Panel: 4-wire Resistive
- Operation Temp.: -20°C to 70°C
- Storage Temp.: -30° to 80°C
- VDD=3.0V to 3.6V



DWN.	YDY	TITLE	LCM OUTLINE DIMENSION		
CHK.	LYJ	PART NO.	LT035A-02AT		
APPD.	LY	DWG. NO.	LT035A-02AT-WXC		
REV.	C	UNIT	mm	PROJECTION	
DATE	2018.03.20	SCALE	NTS	SHEET	1 OF 1